

## MAXX TP5 C

portable sampler as compact device with integrated distributor and 24 bottles for fully automatic sampling according to the vacuum or peristaltic-pump principle.

Battery—operated 12V/10Ah.

Type	Portable sampler
Housing	PE / PC (GF10)
Thermostatic control	Insulated lower part (sample compartment) (insulation thickness 40 mm) Option: freezer packs (200x10x8 mm) Option: compressor cooling (12V/115V/230V)
Control	Microprocessor control, Sleep-Mode (<5mA), power supply 8-16 V foil keyboard (with keys 0-9, ESC, ENT, cursor), graphical display (128*64 Pixel), back lit
Data logger	3000 entries, non-volatile data memory; storage of sampling and malfunction data like sample extractions, bottle changes, messages, external signals. optional with WEB-board 100 MB (2 Year ring memory-FIFO at 1 min interval)
Programming	12 freely programmable user programs, with function to link programs.
Program start options	- IMMEDIATELY; - DATE/TIME - WEEKDAY/TIME; - BY AN EXTERNAL SIGNAL
Program End/Stop options	End of sampling program - AFTER 1 RUN - AFTER X RUNS - CONTINUOUS OPERATION - DATE/TIME
Pause mode	Interruption of program run at any time
Overfilling protection	Adjustable from 1–999 samples/bottles
Interval setting	1 min. to 99 h 59 min. in steps of 1 minute
Pulse setting	1 to 9999 pulses/sample
Manual sample extraction	Possible at any time without interrupting the current program run
Program protection	Up to 5 years after voltage loss
Interface	Mini-USB, RS 232 optional: Ethernet RJ45, SDI-12
Communication (option)	<b>LAN / WLAN / GPRS-UMTS</b> optional: <b>1. Connection via USB and PC</b> • maxxwareConnect® <b>has to be</b> installed on the PC • Connection to the sampler via USB/MiniUSB cable • remote control of the sampler • visualization of downloaded data • download and saving of data as PDF, CSV or XLSX Format • print-out of data directly as PDF Format • backup of all preprogramed programs from the sampler • setting and saving of programs in offline mode. Upload in online mode • Read out, changing, saving or upload of all sampler programs (1-12 ) • recovery of saved programs.  <b>2. LAN Modul RJ45</b> via TCP/IP and IE-Browser • ARM9-SoC

	<ul style="list-style-type: none"> <li>• 32MB RAM</li> <li>• 100 MB Data Memory ((2 Year ring memory-FIFO at 1 min interval)</li> <li>• Linux OS</li> <li>• TCP/IP (RJ45)</li> <li>• recording of all CPU Data (like data of sampling cycle, bottle report, error log, temperature etc.)</li> <li>• visualization via Web interface</li> <li>• Data-export (PDF, CSV, XLS)</li> <li>• E-Mail error messaging</li> </ul> <p><u>or alternatively</u></p> <p><b>3. LAN Modul RJ45 + GPRS/UMTS Router</b></p> <ul style="list-style-type: none"> <li>• ARM9-SoC</li> <li>• 32MB RAM</li> <li>• 100 MB Data Memory ((2 Year ring memory-FIFO at 1 min interval)</li> <li>• Linux OS</li> <li>• TCP/IP (RJ45)</li> <li>• recording of all CPU Data (like data of sampling cycle, bottle report, error log, temperature etc.)</li> <li>• visualization via Web interface</li> <li>• Data-export (PDF, CSV, XLS)</li> <li>• E-Mail error messaging</li> </ul> <p>additionally</p> <ul style="list-style-type: none"> <li>+ Fully integrated Router (industrial standard)</li> <li>+ UMTS / GPRS</li> <li>+ SIM card holder</li> <li>+ E-Mail error messaging</li> <li>+ antenna</li> </ul>
Languages	Multi-language, selectable
Signal inputs	<ul style="list-style-type: none"> <li>• 2 x analogue: 0/4-20 mA,</li> <li>• 8 x digital (flow, event, 1 inputs can be programmed freely)</li> </ul> <p>option: expandable with 4x digital, 3 inputs can be programmed freely, and 8x analogue 0- 20 mA or 0-10 V, Impulslength 60ms, switching level 7-24 V, max. working resistance 500 Ohm, max. length of signalcable 30 m</p>
Signal outputs / status messages	<ul style="list-style-type: none"> <li>• 8 digital outputs,</li> </ul> <p>1x of them as collective malfunction message (Relay optional) option: expandable with 8 digital, 5 are freely programmable (in total 6 messages)</p>
Sampling method	<p>-Vacuum system 20-350 ml -Vacuum VAR (variable) system 5-250 ml Option: peristaltic pump 10-10.000 ml (flow-proportional)</p>
Single sample volume accuracy	<p>Vacuum system: &lt; 2,5 % or +/- 3 ml Peristaltic pump: +/- 5 % or +/- 5 ml</p>
Suction height	<p>Max. 6,5 m (at 1013h Pa) optional 8,5 m or 15 m (Power Booster)</p>
Pumping speed	>0,5 m/s at suction height up to 5 m (at 1013h Pa); pump capacity can be adjusted electronically
Suction hose	PVC, L=5 m, ID=10 mm max. hose length 30 m

Sampling modes	Time-related, flow-dependent, event- related and manual sample extraction. Option: flow-proportional (for Peristaltic Pump as standard)
Bottle variants	1 x 10 L PE 1 x 25 L PE 2 x 13 L PE 4 x 5 L PE 16 x 1 L PE incl. freezer packs 24 x 1 L PE (standard version)
Overall dimensions	(Hxwx d) 787 x 510 x 468 mm /Insulating box passive  1028 x 550 x 468 mm / Insulating box active (with compressor cooling)
Weight	Approx. 25 kg 24x1 L - <b>Isobox with passive cooling</b> Approx. 40 kg 24x1L - <b>Isobox with compressor cooling</b> (device incl. battery, empty bottles but no suction hose)
Power supply	<b>Sampler:</b> 12 V/ 10 Ah lead storage battery (maintenance-free, leak proof); 115V or 230V operation by means of battery charger in buffer mode. Range 11-14V; power consumption max. 30 W <b>Cooling Box:</b> 230V 50 Hz (115V by request) or 12V battery (solar battery with at least 90 Ah)
Power requirement / number of samples	<b>Sampler:</b> Up to 2000 sample extractions per battery charge, according to ambient conditions. <b>Cooling Box:</b> Power requirement with option "active cooling" approx. ... according to ambient conditions. Aprox.. 50W. <b>(with 90 Ah battery, 20°C ambient, sampling 3x/h = running time of cooling system aprox. 49h)</b>
Ambient temperature	0 – 45° C
Sample temperature	0 – 40° C
Standards	CE Sampling according to ISO 5667-10, EN16479
Wetted materials	PC, PVC, Silicone, PS, PE

Make: **MAXX**

Type: **TP5 C**

Manufacturer: MAXX Mess- und Probenahmetechnik GmbH,  
Hechinger Straße 41, D-72414 Rangendingen  
Phone +49(0)7471-98481 0 Fax +49(0)7471-98481 44  
**e-mail: [info@maxx-gmbh.com](mailto:info@maxx-gmbh.com)**  
**internet [www.maxx-gmbh.com](http://www.maxx-gmbh.com)**

Subject to technical changes.

\*) Patent No. DE 19726550A1, DE 19726549A1 and VAR (variable) unit DE 10008623.3